

## THE TATA PIGMENTS LTD

### **TECHNICAL DATA SHEET**

Revision Date: 19.06.19

### **GENERAL DESCRIPTION:-**

Product Name:Iron Oxide RedType:Red PigmentShade:Red Oxide T-130

**Chemical Class** : Synthetic iron oxide  $\alpha$ -Fe2O3

**Delivery Form** : Powder

Color Index : Pigment Red (77491)
CI Name : Pigment Red 101

CAS : 1309-37-1 EINECS NO. : 215-570-8 Particle Shape : Hexagonal

#### ABSOLUTE COLOUR VALUES

Full Shade		Tint Shade		
Binder – Test Paste made by Alkyd		Binder – Test Paste made by Alkyd Resin(Non		
Resin (Non Drying)		Drying)		
L	37.581	Tinted with Titanium Dioxide Rutile, grade 822		
A	29.767	(1:3)	54.430	
В	20.782	A	24.107	
С	36.304	B	10.107	
Н	34.907	С	26.140	
DE compared with T-130	1 max	Н	22.737	
std		DE compared with T-130 std	1 max	
		Relative Tinting Strength	95 - 105	

#### **CHEMICAL PROPERTIES:**

Parameters	Specifications	Test Method
Content of Fe2O3, %	94 min.	IS 44:1991, ANNEX-B, Table1, Sl.
		No-(ix)
PH Value	4-7	IS 33:1992 21
Oil Absorption, %	20-25	IS 33:1992 10
Residue on 325 mesh, %	0.5 max.	IS 33:1992 9
Water soluble, % by mass	0.5 max.	IS 33:1992 19
Volatite at 100±5°C, % by mass	1.0 max.	IS 33:1992 8
Bulk Density, gm/cc	1-1.2	IS 33:1992 17



# THE TATA PIGMENTS LTD

Relative Density	4.3-4.6	IS 33:1992 16	
Acidity (as H2SO4), %	0.1, max	IS 33:1992 18	
Ferrous Iron (as FeO), %	1.5, max	IS 44:1991, ANNEX-C, Table1, Sl.	
		No-(x)	
Calcium Compounds (as CaO), %	2.25 max	IS 44:1991, ANNEX-E, Table1, Sl.	
		No-(xii)	
Water wettability	Passed	ASTM C979 7.1	
Alkali resistance	Resistant	ASTM C979 7.2	
Total Sulfates	0.05 - 0.13%	ASTM C979 7.3	
Atmospheric Curing Stability	Resistant	ASTM C979 7.5	
Light Resistance	Resistant	ASTM C979 7.6	
Effects on Concrete			
A. 28-days Compressive Strength	106.5%	ASTM C979 7.7.5	
B. B. Initial or Final Set	I* -25	ASTM C979 7.7.3	
	F* -10		
Color Match of Shipment	DE* ≤ 1	ASTM C979 7.8	

## **Legends:**

DE\* = Colour Difference according to CIELAB

I\* = Deviation in Minutes Initial

 $F^* = Deviation in Minutes Final$ 

Standard = -60/+90

## **APPLICATIONS**

Industrial Coating	Emulsion Paints	Roof tile Coating	Powder Coating
Decorative Paints	Paints & Coatings	Coil Coating	Wood Coating
Automotive	Plastic and Rubber	Wood Plastic Composites	Corrosion Protection
Coating	polymers		
Leather Industry	Textile Industry	Plaster	Sand – Lime Bricks
Mortar	Masterbatches	Paver	Tiles
Ceramic			



# THE TATA PIGMENTS LTD



**Package:** - 25kg bag HDPE bags

Mohua Siinhababu

Dy Manager(R&D & TS)