

(Trader Exporters importers in Heavy Chemicals, Acids, Dyes, Solvents, Auxiliaries, Minerals)

No.7, Thiruverkadu Main Road, Near Ambattur Industrial Estate, Ayapakkam, Chennai-600 077 Tamilnadu State-South India Ph No.91-044-26820071 Cell No.9444007960

E-mails: sales@pentagonchemical.com & contact@pentagonchemical.com pentagonchemicalss@gmail.com

www.pentagonchemical.com

SPECIFICATIONS of BLEACHING POWDER

- 1.The material shall be white to slightly yellowish –white in appreance and shall be free from hard lumps and any visible impurities. It shall be dry and free flowing.
- 2.The material shall evolve chlorine copiously on the additional of 2 mol/1 solution of Hydrochloric Acid. When the material is shaken with the water and filtered, the filtrate shall yield the two reactions prescribed in Appendix B of SLS 759: 1986, which is authentic for Calcium Salts and Chlorides.
- 3. REQUIREMENT FOR CHLORINATED LIME & CALCIUM HYDROCHLORITE.

Characteristics	Chlorinated Grade 1	
Available chlorine mass	34-35.0%	
Loss of available chlorine on heating		
on the basis of initial available chlorine mass	6.6%, max	
Moisture, mass	0.3%, max	
Particle size (a) Particle passing through		
1.70 mm sieve, mass	99.5%, min	
Bulk density (g/ml.)	0.8, min.	

Packing:

- 1. 25 Kgs HDPE Bag
- 2. The material shall be packed in air- tight, galvanized steel drums (50-Kgs.) made out of guage galvanized sheet with suitable inner –linings or other similar containers but minimum order should be 16 MT attain time